



650V N沟道增强型超结功率场效应管

650V N-CHANNEL Super-Junction POWER MOSFET
11A/650V

Discription

JXM65R380F This N-Channel enhancement mode power MOSFET is produced using advanced Super Junction technology. It achieves low conduction loss and switching losses. It leads the design engineers to their power converters with high efficiency, high power density, and superior thermal behavior. Furthermore, it's universal applicable, i.e., suitable for hard and soft switching topologies.

Features



- $V_{DS}=650V, I_D=11A$
 - $R_{DS(on) (max.)}=380 m\Omega @ V_{GS}=10V$
 - New revolutionary high voltage technology
 - Ultra low gate charge
 - High peak current capability
- 100% UIS TESTED!**
100% ΔVds TESTED!

Applications

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- LED lighting power

Note

- Products made by JUXIN semiconductor



ITO-220AB

ORDERING INFORMATION

Part No.	Package	Marking	Material	Packing
JXM65R380F	ITO-220AB	JXM65R380F	Pb free	Tube

ABSOLUTE MAXIMUM RATINGS (T_J=25°C unless otherwise noted)

Characteristics	Symbol	Ratings	Unit
Drain-Source Voltagee($V_{GS}=0V$)	V_{DS}	650	V
Gate-Source Voltagee	V_{GS}	±20	V
Gate-Source Voltagee($V_{DS}=0V$), AC($f>1HZ$)	V_{GS}	±30	V
Continuous Drain Current	I_D	$T_C=25^\circ C$	11
		$T_C=100^\circ C$	7
Drain Current Pulsed(Note 1)	I_{DM}	44	A
Power Dissipation (T _C =25°C)	PD	-Derate	23
			0.19
Single Pulsed Avalanche Energy (Note 2)	E_{AS}	166	mJ
Reverse Diode dv/dt, $V_{DS}\leq 480V$ (Note 3)	dv/dt	15	V/ns
Drain Source Voltage Slope, $V_{DS}\leq 480V$	dVds/dt	50	V/ns
Operation Junction Temperature Range	T_J	-55 to+150	°C
Storage Temperature Range	T_{STG}	-55 to+150	°C



THERMAL CHARACTERISTICS

Characteristics	Symbol	MAX	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	5.4	°C/W
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	°C/W
Soldering Temperature, Wave Soldering only Allowed at Leads. (1.6mm from Case for 10s)	T_{sold}	260	°C

ELECTRICAL CHARACTERISTICS

Off Characteristics

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Drain -Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	650	--	--	V
Drain-Source Leakage Current	I_{DSS}	$V_{DS}=650V, V_{GS}=0V, T_J = 25^\circ C$	--	--	1.0	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=+20V, V_{DS}=0V$	--	--	100	nA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=-20V, V_{DS}=0V$	--	--	-100	nA

On Characteristics

Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}, I_D=250\mu A$	2.5	3.7	4.5	V
Static Drain- Source On State Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=5.5A$	--	0.32	0.38	Ω
Gate resistance	R_g	$f=1MHz$	--	3.1	--	Ω

Dynamic Characteristics

Input Capacitance	C_{iss}	$V_{DS}=100V, V_{GS}=0V, f=1MHz$	--	678	--	pF
Output Capacitance	C_{oss}		--	30	--	
Reverse Transfer Capacitance	C_{rss}		--	0.9	--	

Switching Characteristics

Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=325V, V_{GS}=10V, R_G=25\Omega, I_D=11A$ (Note 4,5)	--	14	--	ns
Turn-on Rise Time	t_r		--	36	--	
Turn-off Delay Time	$t_{d(off)}$		--	48	--	
Turn-off Fall Time	t_f		--	28	--	
Total Gate Charge	Q_g	$V_{DD}=520V, V_{GS}=0 \text{ to } 10V, I_D=11A$ (Note 4,5)	--	20	--	nC
Gate-Source Charge	Q_{gs}		--	5.7	--	
Gate-Drain Charge	Q_{gd}		--	10	--	

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Continuous Source Current	I_S	Integral Reverse P-N Junction Diode in the MOSFET	--	--	11	A
Pulsed Source Current	I_{SM}		--	--	44	
Diode Forward Voltage	V_{SD}	$I_S=11A, V_{GS}=0V$	--	0.9	1.4	V
Reverse Recovery Time	T_{rr}	$I_S=11A, V_{GS}=0V, di/dt=100A/\mu S$	--	276	--	ns
Reverse Recovery Charge	Q_{rr}		--	3.34	--	μC

- 注:
1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
 2. E_{AS} condition: Starting $T_J=25^\circ C, V_{DD}=50V, V_G=10V, R_G=25\Omega$.
 3. $I_{SD} \leq I_D, di/dt \leq 200A/\mu s, V_{DD} \leq BV_{DSS}$, Starting $T_J=25^\circ C$.
 4. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycles $\leq 2\%$.
 5. Essentially Independent of Operating Temperature Typical Characteristics.

典型特性曲线

Fig.1: Output Characteristics




Fig.2: Typical Transfer Characteristics




Fig.3: Typical On-resistance vs. Drain Current




Fig.4: Typical Body Diode Forward Voltage




Fig.5: Typical Capacitance Characteristics





Fig.6: Typical Gate Charge Characteristics



典型特性曲线

Fig.7: Normalized Breakdown Voltage vs. Junction Temperature




Fig.8: Normalized on Resistance vs. Junction Temperature







Fig.9: Maximum Safe Operating Area





Test Circuit



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveform




Unclamped Inductive Switching Test Circuit & Waveform



Package Dimensions of ITO-220AB

Package Dimensions of ITO-220AB

Unit:mm



SYMBOL	MILIMETER	
	MIN	MAX
A	4.20	4.95
A1	2.24	3.10
A3	2.30	3.30
b	0.60	1.00
b2	1.15	1.55
c	0.35	0.65
D	14.80	16.40
D1	15.00	17.00
D2	8.80	11.60
E	9.70	10.60
e	2.54BSC	
H1	6.00	7.40
L	11.40	15.10
L1	2.60	4.50
Φ P	2.90	3.40
Q	3.00	3.70

Legal Disclaimer Notice

All specifications are subject to be changed without notice to improve reliability function, design, etc. JUXIN makes no warranty, or guarantee regarding the suitability of the products for any purpose. To the extent permitted by applicable law, JUXIN disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement.

Statements regarding the suitability of products for certain types of applications are based on JUXIN's ideas of typical requirements that are often placed on JUXIN products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and specifications may differ applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify JUXIN's terms and conditions of purchase, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, JUXIN products are not designed for use in medical, life saving, or life-sustaining applications or for any other applications in which the failure of the JUXIN product could result in personal injury or death. Customers using or selling JUXIN products not expressly indicated for use in such applications do so at their own risk. Please contact authorized JUXIN personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by forbid or otherwise, to any intellectual property rights is granted by this document or by any conduct of JUXIN. Product names and markings noted herein may be trademarks of their respective owners.