

**Single Phase Glass Passivated
Fast Recovery Bridge Rectifiers**

**Reverse Voltage: 50V to 1000V
Forward Current: 4.0 Amp**

Features


- Glass passivated chip junction
- Ideal for automated placement
- Low leakage current
- High forward surge capability
- Moisture sensitivity level: level 1, per J-STD-020

Mechanical Data

- **Package:** DBF
Molding compound meets UL 94 V-0 flammability rating
- **Terminals:** Matte tin plated leads,
solderable per MIL-STD-750, Method 2026
- **Polarity:** Symbol marking on body

Typical Applications

Suitable for AC to DC bridge full wave rectification for SMPS, LED lighting, adapter, battery charger, home appliances, office equipment, and telecommunication applications.



Package Outline Dimensions in Inches (Millimeters)

Maximum Ratings and Electrical Characteristics (Ta=25°C Unless otherwise specified)

Parameter&Test Conditions	SYM.	RDBF 4005	RDBF 401	RDBF 402	RDBF 404	RDBF 406	RDBF 408	RDBF 410	Unit
Device marking code		RDBF4005	RDBF401	RDBF402	RDBF404	RDBF406	RDBF408	RDBF410	
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	V
Maximum Average Forward Output Rectified Current (see Fig. 1)	IO(AV)	4.0							A
Peak Forward Surge Current 8.3ms Single Half Sine-wave Superimposed On Rated Load	IFSM	125							A
Operating junction range	Tj	-55 to+150							°C
Storage temperature range	TSTG	-55 to+150							°C

Thermal Characteristics (Ta=25°C Unless otherwise specified)

Parameter&Test Conditions	SYM.	RDBF 4005	RDBF 401	RDBF 402	RDBF 404	RDBF 406	RDBF 408	RDBF 410	Unit
Maximum Thermal Resistance per Leg, Junction To Lead (Note 1)	RθJL	15							°C/W
Maximum Thermal Resistance per Leg, Junction To Ambient (Note 1)	RθJA	55							°C/W

Electrical Characteristics (Ta=25°C Unless otherwise specified)

Parameter&Test Conditions	SYM.	RDBF 4005	RDBF 401	RDBF 402	RDBF 404	RDBF 406	RDBF 408	RDBF 410	Unit
Maximum reverse recovery time IF=0.5A, IR=-1.0A, IRR=-0.25A	Trr	150				250	500		ns
Maximum Instantaneous Forward Voltage per diode IF= 4A	VFM	1.30							V
Maximum DC reverse current at rated DC blocking voltage per diode	TA = 25°C	5							µA
	TA = 125°C	200							

Notes:
1. Units mounted on PCB (16mm x 16mm Cu pad test board).

Rating and Characteristic Curves

FIG. 1- DERATING CURVE OUTPUT RECTIFIED




FIG. 2- -MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT Per Diode




FIG. 3- TYPICAL FORWARD VOLTAGE





FIG. 4- TYPICAL REVERSE LEAKAGE CHARACTERISTICS



The curve above is for reference only.



Legal Disclaimer Notice

All specifications are subject to be changed without notice to improve reliability function, design, etc. JUXIN makes no warranty, or guarantee regarding the suitability of the products for any purpose. To the extent permitted by applicable law, JUXIN disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement.

Statements regarding the suitability of products for certain types of applications are based on JUXIN's ideas of typical requirements that are often placed on JUXIN products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and specifications may differ for different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify JUXIN's terms and conditions of purchase, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, JUXIN products are not designed for use in medical, life saving, or life-sustaining applications or for any other applications in which the failure of the JUXIN product could result in personal injury or death. Customers using or selling JUXIN products not expressly indicated for use in such applications do so at their own risk. Please contact authorized JUXIN personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by forbidding or otherwise, to any intellectual property rights is granted by this document or by any conduct of JUXIN. Product names and markings noted herein may be trademarks of their respective owners.